



# Needlepunch Broadloom Carpet Rolls

Installation, Maintenance, & Warranty  
for Roll Goods

## Indoors or Vestibules or Other Enclosed Areas:

### OPTIONS

1. Loose-lay where temporary use is dictated.
2. Loose-lay in recess where frequent mat changes are encouraged.
3. Double-face tape, in areas where semi-permanent use is dictated.
4. Permanent installation method:
  - Use product comparable to APAC-440 \*\* Adhesive w 3/32 sq notch trowel over smooth, moderately porous subfloor. If subfloor is smooth yet highly porous, seal with a1 or 2 coats of product comparable to APAC V-Block or APAC Encapseal to seal porosity of subfloor. Allow to dry/ set/ cure 4-12 hours before troweling product comparable to APAC 440.
  - Allow adhesive to tack-up but not skin over
  - Roll with a 75-100 lb roller.
  - Cut seam net, apply no seam sealer. Minimize use of head seams for best visual appearance.
  - Disallow unprotected foot traffic and all rolling traffic for 12 hours, and disallow unprotected heavy foot / rolling traffic for 48-72 hours.
  - Keep area completely dry for 72 hours.

\*\* substitute product comparable to APAC 564 if area is subject to temperature extremes

## Outdoors:

### OPTIONS

1. Loose-lay in framed or unframed areas where temporary use is dictated.
2. Permanent installation:

If sub-surface is rough or highly porous use appropriate cementacious outdoor-rated product to achieve desire smooth, slightly porous surface. Allow adequate time to cure / dry before going forward with installation.

  - Use product an outdoor, water-based solvent Adhesive w 3/32 sq notch trowel over smooth moderately porous subfloor.
  - Follow temperature and acclimation criteria as outlined by the Adhesive Manufacturer
  - Allow adhesive to tack-up.
  - Roll with a 75-100 lb roller.
  - Cut seams net, apply no seam sealer. Minimize use of head seams for best visual appearance.
  - Protect from elements until adhesive is cured. Follow all directions on adhesive label.
  - Disallow unprotected foot traffic and all rolling traffic for 12 hours, and disallow unprotected heavy foot / rolling traffic for 48-72 hours.

**Maintenance:** Vacuuming, extraction, and shampooing

**Warranties\*:** Five (5) years on smooth flat surfaces. Three (3) years on flat surfaces under cleat and spike traffic.

*\*See Fordom warranty terms*